

Proxima DP9240 Projector

Technical and Functional Specifications

Display Technology	<ul style="list-style-type: none">• 1.3" polysilicon TFT LCD x 3
Resolution	<ul style="list-style-type: none">• XGA (1024 x 768)
Resolutions Supported	<ul style="list-style-type: none">• XGA (1024 x 768); Fit-to-View display of VGA (640 x 480), SVGA (800 x 600), SXGA (1280 x 1024)
Brightness	<ul style="list-style-type: none">• 1600 ANSI lumens
Contrast Ratio	<ul style="list-style-type: none">• 350:1 (full on, full off)
Computer Compatibility	<ul style="list-style-type: none">• IBM PC, PS/2, Pentium and compatibles• SUN, SGI, IBM, HP, DEC• Apple Macintosh, Power Macintosh, and PowerBook families
Video Compatibility	<ul style="list-style-type: none">• NTSC, NTSC 4.3, PAL, PAL-M, SECAM, HDTV (480p, 720p, 1080i, 1035i)
Sources	<ul style="list-style-type: none">• 2 computer, 1 S-video, 1 composite video, 1 component video, audio for computer & video
H-Sync Range	<ul style="list-style-type: none">• 15 to 100 KHz
V-Sync Range	<ul style="list-style-type: none">• 50 to 100 Hz
Dot Clock	<ul style="list-style-type: none">• 165 MHz
Horizontal Resolution	<ul style="list-style-type: none">• 800 TV lines
Aspect Ratio	<ul style="list-style-type: none">• std: 4:3 - wide: 16:9
Image Size Diagonal	<ul style="list-style-type: none">• 2.5 ft to 25 ft (.76 m to 7.6 m)
Projection Lens (Standard)	<ul style="list-style-type: none">• Power zoom and focus lens, 1.3:1 zoom ratio• Focal length: 48.4 mm to 62.8 mm, F 1.8 to F 2.1
Throw Ratio	<ul style="list-style-type: none">• 1.8 - 2.4:1
Projection Distance (From Screen)	<ul style="list-style-type: none">• 4.6 ft to 35.4 ft (1.4 m to 10.8 m)
Keystone Correction (Optical)	<ul style="list-style-type: none">• 11° fixed
Keystone Correction (Digital)	<ul style="list-style-type: none">• + 30° adjustable
Number of Colors	<ul style="list-style-type: none">• 16.7 million
Lamp	<ul style="list-style-type: none">• 200-watt UHP
Audio	<ul style="list-style-type: none">• 2-watt stereo
Remote Control	<ul style="list-style-type: none">• Wireless IR remote with mouse control and laser pointer
RS-232 Control	<ul style="list-style-type: none">• Bi-direction communication
Dimensions	<ul style="list-style-type: none">• 10.7 in W x 16.2 in L x 6.1 in H• (27.2 cm W x 41.2 cm L x 15.4 cm H)
Weight	<ul style="list-style-type: none">• 15.2 lbs (6.9 kg)
Power Consumption	<ul style="list-style-type: none">• 300 watts
Power Requirements	<ul style="list-style-type: none">• 100 to 120V / 220 to 240V at 50/60 Hz
Operating Temperature (Sea Level)	<ul style="list-style-type: none">• 41° to 95° F (5° to 35° C)
Approvals	<ul style="list-style-type: none">• FCC Class A, UL, c-UL, CE
Warranty	<ul style="list-style-type: none">• Two years parts and labor (excluding lamp)• 90-day limited on lamp